



Specifications:

- Operating temperature, -40°C to +70°C
- Dual terminals
- U/L listed
- 60/50 Hz rated



RUBBER BOOT

Catalogue Number	List Price
BOOT70RCCAP	\$2.50

RUN CAPACITORS • OVAL • 370 VOLT

Mfd.	Width X Depth X Height (Inches)	Catalogue Number	List Price	Ctn.
2	2.16" X 1.31" X 2.17"	ORC2370	\$5.00	50
3	2.16" X 1.31" X 2.17"	ORC3370	5.00	50
4	2.16" X 1.31" X 2.17"	ORC4370	5.00	50
5	2.16" X 1.31" X 2.17"	ORC5370	4.00	50
6	2.16" X 1.31" X 2.17"	ORC6370	5.70	50
7.5	2.16" X 1.31" X 2.17"	ORC7.5370	5.00	50
10	2.16" X 1.31" X 2.56"	ORC10370	6.00	50
12.5	2.16" X 1.31" X 2.95"	ORC12.5370	9.00	50
15	2.16" X 1.31" X 3.10"	ORC15370	9.00	50
17.5	2.91" X 1.89" X 2.56"	ORC17.5370	10.00	50
20	2.91" X 1.89" X 2.56"	ORC20370	10.00	50
25	2.91" X 1.89" X 2.95"	ORC25370	11.00	50
30	2.91" X 1.89" X 2.95"	ORC30370	13.00	50
35	2.91" X 1.89" X 3.54"	ORC35370	12.50	50
40	2.91" X 1.89" X 3.94"	ORC40370	16.50	50
50	2.91" X 1.89" X 3.94"	ORC50370	23.00	50

RUN CAPACITORS • OVAL • 240 VOLT

Mfd.	Width X Depth X Height (Inches)	Catalogue Number	List Price	Ctn.
20	2.17" X 1.31" X 2.95"	ORC20240	\$9.00	-
30	2.17" X 1.31" X 3.54"	ORC30240	12.00	-
35	2.17" X 1.31" X 3.94"	ORC35240	12.00	-
40	2.17" X 1.31" X 3.94"	ORC40240	14.50	-
50	2.91" X 1.89" X 2.95"	ORC50240	18.00	-
65	2.91" X 1.89" X 3.35"	ORC65240	23.50	-



RUN CAPACITORS • OVAL • 440 VOLT

Mfd.	Width X Depth X Height (Inches)	Catalogue Number	List Price	Ctn.
2	2.16" X 1.31" X 2.17"	ORC2440	\$6.00	50
3	2.16" X 1.31" X 2.17"	ORC3440	6.00	50
4	2.16" X 1.31" X 2.17"	ORC4440	6.00	50
5	2.16" X 1.31" X 2.17"	ORC5440	6.00	50
6	2.16" X 1.31" X 2.56"	ORC6440	7.80	50
7.5	2.16" X 1.31" X 2.56"	ORC7.5440	7.50	50
10	2.16" X 1.31" X 3.35"	ORC10440	8.80	50
12.5	2.91" X 1.89" X 2.56"	ORC12.5440	9.80	50
15	2.91" X 1.89" X 2.56"	ORC15440	10.50	50
17.5	2.91" X 1.89" X 2.95"	ORC17.5440	12.00	50
20	2.91" X 1.89" X 2.95"	ORC20440	13.00	50
25	2.91" X 1.89" X 3.54"	ORC25440	15.00	50
30	2.91" X 1.89" X 3.74"	ORC30440	17.00	50
35	2.91" X 1.89" X 4.33"	ORC35440	16.00	50
40	2.91" X 1.89" X 4.72"	ORC40440	17.50	50
45	3.65" X 1.97" X 3.74"	ORC45440	18.60	50
50	3.65" X 1.97" X 3.74"	ORC50440	23.70	50
55	3.65" X 1.97" X 4.72"	ORC55440	23.00	50
60	3.65" X 1.97" X 4.72"	ORC60440	30.50	50

RUN CAPACITORS • ROUND • 370 VOLT

Mfd.	Diameter X Height (Inches)	Catalogue Number	List Price	Ctn.
3	1.75" X 2.88"	X386S3.0370	\$9.00	50
4	1.75" X 2.88"	X386S4.0370	9.00	50
5	1.75" X 2.88"	X386S5.0370	9.00	50
7.5	1.75" X 2.88"	X386S7.5370	10.00	50
10	1.75" X 2.88"	X386S10.0370	10.00	50
12.5	1.75" X 2.88"	X386S12.5370	11.00	50
15	1.75" X 2.88"	X386S15.0370	11.00	50
17.5	1.75" X 2.88"	X386S17.5370	13.00	50
20	1.75" X 2.88"	X386S20.0370	13.50	50
25	1.75" X 2.88"	X386S25.0370	14.50	50
30	1.75" X 4.75"	X386S30.0370	16.00	50
35	2.00" X 4.75"	X386S35.0370	17.50	50
40	2.00" X 4.75"	X386S40.0370	19.50	50
45	2.00" X 4.75"	X386S45.0370	22.00	50
50	2.50" X 4.75"	X386S50.0370	24.00	25

RUN CAPACITORS • ROUND • 240-370 VOLT

Replacement Capacitors For PERFORMA + Motors

Mfd.	Width X Depth X Height (Inches)	Catalogue Number	List Price	Volts
20	1.81" X 1.77"	RP20240	\$7.50	240
25	1.81" X 1.77"	RP25240	9.00	240
35	1.81" X 1.77"	RP35240	12.50	240
25	1.81" X 1.77"	RP25370	11.00	370

Catalogue numbers in blue are NEW items.



Accessories

Specifications:

- Operating temperature, -40°C to +65°C
- Moisture and oil resistant case requiring no insulation
- Dual terminals
- U/L listed
- Conforms to EIA RS 463 standards for Type 1 and Type 2 capacitors
- 60/50 Hz rated [min. 47 Hz, max. 66 Hz]

START CAPACITORS • 110-125 VOLT

Mfd.	Diameter X Height (Inches)	Catalogue Number	List Price	Ctn.
108-130	1.438" X 2.750"	SC108B125-1	\$4.50	100
124-149	1.438" X 2.750"	SC124B125-1	4.60	100
130-156	1.438" X 2.750"	SC130B125-1	4.70	100
161-193	1.438" X 2.750"	SC161B125-1	4.90	100
189-227	1.438" X 2.750"	SC189B125-1	5.00	100
216-259	1.438" X 2.750"	SC216B125-1	5.25	100
270-324	1.438" X 2.750"	SC270B125-1	5.70	100
324-388	1.813" X 3.375"	SC324B125-4	7.75	64
340-408	1.813" X 3.375"	SC340B125-4	8.00	64
400-480	1.813" X 3.375"	SC400B125-4	8.30	64
460-552	1.813" X 3.375"	SC460B125-4	8.70	64
540-648	1.813" X 4.375"	SC540B125-5	10.00	64
590-708	1.813" X 4.375"	SC590B125-5	10.40	64
708-850	2.063" X 4.375"	SC708B125-7	11.30	49
1000-1200	2.063" X 4.375"	SC999B125-7	15.75	49

START CAPACITORS • 220-250 VOLT

Mfd.	Diameter X Height (Inches)	Catalogue Number	List Price	Ctn.
53-64	1.438" X 3.375"	SC53B250-2	\$7.00	100
88-108	1.813" X 3.375"	SC88B250-4	8.00	64
108-130	1.813" X 3.375"	SC108B250-4	9.00	64
130-156	1.813" X 3.375"	SC130B250-4	9.40	64
161-193	1.813" X 4.375"	SC161B250-5	10.75	49
189-227	2.063" X 3.375"	SC189B250-6	11.60	49
216-259	2.063" X 3.375"	SC216B250-6	13.00	49
233-280	2.063" X 3.375"	SC233B250-6	14.30	49
270-324	2.063" X 3.375"	SC270B250-6	15.20	49
324-389	2.063" X 4.375"	SC324B250-7	20.00	49
340-408	2.063" X 4.375"	SC340B250-7	20.00	49
400-480	2.063" X 4.375"	SC400B250-7	26.00	25
460-552	2.563" X 4.375"	SC460B250-8	28.50	25
630-750	2.563" X 4.375"	SC630B250-8	40.00	25

START CAPACITORS • 330 VOLT

Mfd.	Diameter X Height (Inches)	Catalogue Number	List Price	Ctn.
30-36	1.813" X 3.375"	SC30B330-4	\$9.00	64
53-64	1.813" X 3.375"	SC53B330-4	8.90	64
88-108	1.813" X 4.375"	SC88B330-5	11.25	64
108-130	1.813" X 4.375"	SC108B330-4	12.00	64
130-156	2.063" X 4.375"	SC130B330-7	14.75	49
145-175	2.063" X 4.375"	SC145B330-7	15.25	49
161-193	2.063" X 4.375"	SC161B330-7	15.90	49
189-227	2.063" X 4.375"	SC189B330-7	17.20	49
216-259	2.063" X 4.375"	SC216B330-8	20.75	25

